

Article no.: 300100, 300110, 300115, 300120, 300125

## Description

Hanseline – Bicycle Oil is a hydrocarbon, that is qualified by its purity, it is totally free of acid or resin, for influence of UV- and oxygen only very slowly. So it has excellent aging properties. Due to its low viscosity and its coating capacities it protects the material from corrosion. It is proper for very fast running mechanics because of its low inner resistance.

## Usage

Hanseline – Bicycle oil is made for joints of gearshifters, brake levers and derailleurs. Clean lubricating points, remove old lubricants. Apply and let affect shortly. After a short term running, lubricate again. When lubricating Bowden wires: dismantle the cables and apply some drops between cover and cable. Regular application maintains the functioning.



## Technical Data

form:	fluid
color:	bright
odour:	characteristic
Pourpoint (DIN/ISO 3016):	Pourpoint -12°C
Flashpoint (DIN/ISO 2592):	200°C
Density at 15°C (DIN 51757):	0,86 g/ml
Viscosity at 40°C (DIN 51562 part 1):	> 20,5 mm <sup>2</sup> /s

Specifications are subject to change without notice! All information provided was researched and processed to the best of our knowledge, liability excluded. For further information contact our technical service.

## TARIC

2710 19 85

## Packaging



100; 500ml



1l



5l

10 or 50 per  
inner carton in  
outer carton of 200

cartons of 10

cartons of 4